

SPARTAN PLUS 80NB

PRODUCT NAME	SPARTAN PLUS 80NB		88.9MM		
Mode	Locking & Removable	Locking & Removable	Fixed Situ	Fixed Situ	Wall Thickness
Specification Model	SPT90R-ST-W10	SPTG90R-ST-W10	SPT90F-ST-W10	SPTG90F-ST-W10	10.4mm
Height above ground	900mm	1200mm	900mm	1200mm	-
Material	Extra heavy duty galvanised pipe + heavy duty galvanised insert				
Nominal Bore (NB)	80NB				
Outside Diameter	88.9mm				
Finish	Electrostatically Powdercoated in a range of colours. Standard colours are: ● ●				
Options & Accessories	Fit High Security BiLock / Abloy Locks, Class 1 & 2 Reflective Tape, Hinged or standard Cover Plates, Cast in Sleeve. Hot Dip Galvanising				
Recommended Accessories	(Cover Plate SDCP80) – (InGround Sleeve SLV80R) Secure Storage Holder (Single SSH1) (Double SSH2)				
Installation	<ul style="list-style-type: none"> ◆ Retro fit into existing concrete slab with minimum 200mm thickness. ◆ We recommend using a sleeve where concrete depth is less than 200mm or when installing into pavers, bitumen ◆ We recommend installing into a reinforced concrete footing 400x400x500deep. ◆ Strip footing also recommended when all in line. 				

