

## VOGUE 150NB

PRODUCT NAME   VOGUE 150NB   168.3mm O.D.					
Mode	Locking & Removable	Fixed Insitu	Fixed Baseplate	Screw-Down Indoor Bollard	Wall Thickness
Specification Model	V0G150R-SS4-W3	V0G150F-SS4- W3	V0G150B-SS4-W3	V0G150FS-SS4-W3	3.40mm
Specification Model	V0G150R-SS4-W7	V0G150F-SS4-W7	-	-	7.11mm
Specification Model	V0G150R-SS4-W10	VOG150F-SS4-W10	-	-	10.97mm
Material	Stainless Steel Grade 304 (SS4) (Grade 316 Stainless Steel available. (Substitute SS6 to specification model))				
Nominal Bore (NB)	150NB				
Outside Diameter	168.3mm				
Finish	Linished or Electro Polished				
Options & Accessories	Fit High Security BiLock / Abloy Locks, Class 1 & 2 Reflective Tape, Hinged or standard Cover Plates, Cast In Sleeve, Hot Dip Galvanising. Bronze motif with your company logo. Laser engraving available				
Installation	<ul> <li>Retro fit into existing concrete slab with minimum 200mm thickness</li> <li>We recommend using a sleeve where concrete depth is less than 200mm or when installing into pavers, bitumen ◆ We recommend installing into a reinforced concrete footing 400x400x500 deep ◆ Strip footing also recommended when all in line.</li> </ul>				



