

VOGUE 80NB CHAMFERED

1300 450 650 LOCAL AREA PROTECTIVE SERVICES

PRODUCT NAME VOGUE 80NB CHAMFERED 88.9mm O.D.					
Mode	Locking & Removable	Fixed Insitu	Fixed Baseplate	Screw-Down Indoor Bollard	Wall Thickness
Specification Model	VOGC80R-SS4-W3	VOGC80F-SS4- W3	VOGC80B-SS4-W3	VOGC80FS-SS4-W3	3.05mm
Specification Model	VOGC80R-SS4-W5	VOGC80F-SS4-W5	-	-	5.49mm
Specification Model	VOGC80R-SS4-W7	VOGC80F-SS4- W7	-	-	7.62mm
Material	Stainless Steel Grade 304 (Grade 316 Stainless Steel available Models - Substitute 'SS6' to specification model)				
Nominal Bore (NB)	80NB				
Outside Diameter	88.9mm				
Finish	Linished or Electro Polished				
Options & Accessories	Fit High Security BiLock / Abloy Locks, Class 1 & 2 Reflective Tape, Hinged or Standard Cover Plates, Cast In Sleeve. Bronze motif with your company logo. Laser engraving available				
Installation	 Retro fit into existing concrete slab with minimum 200mm thickness We recommend using a sleeve where concrete depth is less than 200mm or when installing into pavers, bitumen → We recommend installing into a reinforced concrete footing 350x350x500 deep → Strip footing also recommended when all in line. 				



