VOGUE 80NB

OI

SECURITY



PRODUCT NAME VOGUE 80NB 89.9mm O.D.					
Mode	Locking & Removable	Fixed Insitu	Fixed Baseplate	Screw-Down Indoor Bollard	Wall Thickness
Specification Model	VOG80R-SS4-W3	VOG80F-SS4- W3	VOG80B-SS4-W3	VOG80FS-SS4-W3	3.05mm
Specification Model	VOG80R-SS4-W5	VOG80F-SS4- W5	-	-	5.49mm
Specification Model	VOG80R-SS4-W7	V0G80F-SS4- W7	-	-	7.62mm
Material	Stainless Steel Grade 304 (Grade 316 Stainless Steel available Models - add SS6 to specification model)				
Nominal Bore (NB)	80NB				
Outside Diameter	88.9mm				
Finish	Linished or Electro Polished				
Options & Accessories	Fit High Security BiLock / Abloy Locks, Class1 & 2 Reflective Tape, Hinged or standard Cover Plates, Cast In Sleeve, Hot Dip Galvanising				
Installation	 Retro fit into existing concrete slab with minimum 200mm thickness We recommend using a sleeve where concrete depth is less than 200mm or when installing into pavers, bitumen We recommend installing into a reinforced concrete footing 350x350x500 deep Strip footing also recommended when all in line. 				
Removable Top view: Optional Bronze motif with your logo 900 200	1 2 2	Baseplate s	Unique Istallation requires a ingle M20 anchor erew-down Istallation (150 150 150 150 150 150 150	ghting Retracta	lels ible r to ible