## ELECTRA ENCLOSURE 200NB POWER & WATER BOLLARDS



PRODUCT NAME   ELECTRA ENCLOSURE 200NB POWER & WATER BOLLARDS			
Mode	Baseplate Fixed Single Door	Baseplate Fixed Double Door	Wall Thickness (pipe)
Steel Model #	ELE201B-ST	ELE202B-ST-PW	4.8mm
Stainless Steel Model #	ELE201B-SS4 to S	ange S6 for ELE202B-SS4-PW Cha to P	nge 3.76mm P for
Steel with Vandal Door Model #	ELE201BV-ST	de 316 ELE202BV-ST-PW Power behin	Power d both 4.8mm
Stainless with Vandal Door Model #	ELE201BV- <mark>SS4</mark>	ELE202BV-SS4-PW	3.76mm
Two door models: Default Service behind each bollard is Power Water. Change to Power+Power (-PP) if bottom door is to be power.			
Nominal Bore (NB)	200NB		
Outside Diameter	Steel 219.1mm   Stainless Steel 219.0mm		
Height Above Ground	1115mm including baseplate		
Material Steel   Stainless Steel	Heavy Duty Galvanised Pipe   Stainless Steel Grade 304 or <b>SS6</b> for Marine Grade 316 Stainless		
Baseplate Dimensions	Diam. 340x 8mm – Four pre-punched holes.		
Mounting Plate (for internal gear)	150mm x 450mm height - 3mm thickness – Galvanised – Pre-punched mounting plate to accommodate 2, 4, 6 & 8 standard mounting enclosures		
Finish - Steel	Hot Dip Galvanised or electrostatically powdercoated in a range of colours		
Finish - Stainless Steel	Linished or electro-polished		
Options & Accessories	Keying Alike, Class 1 or 2 Reflective Tape, Spare backing plate (retrofitting new gear)		
Installation	4 x M12 - 100mm Chemset anchors (Galvanised) or stainless depending on model being installed.		

