EXTREME INDUSTRIAL 150NB - 200NB



PRODUCT NAME EXTREME INDUSTRIAL 150NB - 200NB						
Mode	Removable		Removable		Fixed Insitu	Fixed Baseplate
Nominal Bore (NB)	150NB		200NB		SHS 250x250x9.5m	
Outside Diameter	168.3mm O.D	Wall Thickness	219.1mm O.D.	Wall Thickness	Baseplate 300x450x25mm	
Specification Model#	XTM150R-ST-W7 XTM150R-ST-W11	7.11mm 11.0mm	XTM200R-ST-W8 XTM150R-ST-W12	8.2mm 12.7mm	XTMS250F-ST-W9	XTMS250B-ST-W9
Height above ground	900mm		900mm		1400mm	
Bollard Depth in Ground	300mm		300mm		300mm	-
Recommended RC Footing	600x600x750 deep		750x750x750 deep		1000x1000x1100 deep	
Material	Galvanised steel pipe					
Finish	Straight Galvanised finish or Electrostatically Powdercoated a range of colours Standard colours: Black Industrial Yellow					
Baseplate Size	300 x 450 x 25mm plate welded to SHS all around 300mm 0.D. X 6mm protection ring fixed with masonry anchors minimises concrete slab wear					
Options & Accessories	Class 1 or 2 Reflective Tape, Hot Dip Galvanising, Optional colours available on request					
Installation	◆ Designed for use in extreme industrial applications. ◆ Fixed eyebolt allows lifting					



