

HIGH IMPACT THREAT (HIT) 150NB - 200NB - 300NB

IMPACT SECURITY®
1300 450 650
LAPS.COM.AU LOCAL AREA
PROTECTIVE SERVICES

PRODUCT NAME | High Impact Threat (HIT) 150NB - 200NB - 300NB

Mode	Fixed Insitu					
Nominal Bore (NB)	150NB		200NB		300NB	
Outside Diameter	169.3mm	Wall Thickness	219.1	Wall Thickness	323.9	Wall Thickness
Specification Model #	HIT150F-ST-W4 HIT150F-ST-W7 HIT150F-ST-W11	4.8mm 7.11mm 11.0mm	HIT200F-ST-W4 HIT200F-ST-W8 HIT150F-ST-W12	4.8mm 8.2mm 12.5mm	HIT300F-ST-W6 HIT300F-ST-W9 HIT300F-ST-W12	6.35mm 9.5mm 12.7mm
Recommended RC Footing	600x600x750 deep		750x750x750 deep		900x900x900 deep	
Height above ground	800mm					
Bollard Depth in Ground	600mm					
Material	Extra Heavy duty galvanised pipe					
Finish	Straight Galvanised finish or Electrostatically Powdercoated a range of colours. Standard colours: ● ● Stainless steel Skin Sleeves available for this product.					
Finishing Skins	We have plastic (range of colours) or stainless steel skins which can be fitted over the bollard to provide an alternative finish. (150NB only)					
Options & Accessories	Class1 or 2 Reflective Tape, Hot Dip Galvanising, Optional colours available on request					
Installation	<ul style="list-style-type: none"> ◆ Bollards are designed for concrete filling onsite. ◆ Caps & reinforcement cages not included (POA) 					

